

UT 600 S / UT 2000 S

Rewind Tables

These versatile rewind tables for 35 mm and 16 mm films are an excellent tool for daily work at film archives, post production and printing facilities, etc.

The UT 600 S and UT 2000 S rewind tables satisfy highest demands for reliability and versatility. Their microprocessor controlled drive systems guarantee a smooth film transport with accurate tension control.



Top Features

- » Suitable for 35 mm and 16 mm film on Kodak cores or film spools
- » Microprocessor-controlled drive system
- » Two directly driven discs with accurate film tension control
- » Variable winding speed
- » Winding direction selectable
- » Automatic shut-off on film run-out
- » Digital film counter for frames / length / speed / time
- » Comes with adapter kit for 16 mm and 35 mm film
- » Available for 600 m / 1970 ft of film (UT 600 S) or for 2000 m / 6500 ft of film (UT 2000 S)
- » Solid working plate with large backlit inspection plate
- » Robust frame with lockable castors

Technical Data

Mains Voltage	230 V (optionally 120 V)
Mains Frequency	50 / 60 Hz
Power Input	250 VA
Film Capacity	» UT 600 S: 600 m (1970 ft) of 35 mm or 16 mm film » UT 2000 S: 2000 m (6500 ft) of 35 mm or 16 mm film

See the Difference.



Kinoton GMBH

Photos may show optional equipment. Any individual item is subject to change without notice. The latest version of this brochure can be found on www.kinoton.com.

Kinoton GmbH
Industriestrasse 20a
82110 Germering / Germany
Phone +49 (0)89 894446-0
Fax +49 (0)89 8402002
welcome@kinoton.de
www.kinoton.com